



MP Portable Series

Hand-held pneumatic dot peen markers

REFERENCE MP-PTL SERIES

MODEL:	MP-50-PTL	MP-80-PTL
Marking Window:	1.97" x 1.18" (50 x 30 mm)	3.15" x 1.18" (80 x 30 mm)
Marking Head Technology:	Pneumatic	
Operating Air Pressure:	65 to 85 psi	
Marking Stylus:	Standard LP-10 / HF-16 for ultra-high-speed	
Marking Control:	Plug & play 7" TFT SVGA touch-screen controller with 19.69 ft (6m) cable	
Interfaces:	USB, RS-232/RS-485, IN/OUT, start-stop	
Marking Data:	Alphanumeric text and keyboard symbols, serial numbers, automatic date & time, shift codes, data matrix codes, vector graphics and logos (.PLT)	
Automation:	Data entry via RS-232 Marking control through programmable commands	
Marking Fonts:	Dot matrix formed: 5x7, 7x9, 11x16 Continuous line: Fastflan and standard	
Dimensions (W x D x H):	Marking Head: 4.49" x 8.11" x 10.32"	Marking Head: 5.67" x 8.1" x 10.32"
	Controller: 11.30" x 3.54" x 7.28"	
Weight:	Marking Head: 5 lb 1 oz	Marking Head: 5 lb 5 oz
	Controller: 5 lb 15 oz	
Power Supply:	110/220V; 50/60Hz	
Certification:	CE	
Included Equipment:	<ul style="list-style-type: none"> Start-stop button Air pressure regulator 	
Optional Equipment:	<ul style="list-style-type: none"> Detachable anti-slip flat front mask Benchtop marking column and base Nameplate marking fixture 	