# PortaDot P50-25

Marking Window 50mm x 25mm

Weight 2.3kg

Versatile, lightweight handheld marking machine. Suitable for majority of applications.

Supplied with quick-change facemasks for marking on curved or flat surfaces. Also available with optional long-reach facemask and nosepiece.

Standard 4000 embedded controller provides full range of marking and control features. Optional battery powered version available.



#### STANDARD FEATURES

- 4000 Embedded Controller
- Electromagnetic solenoid driven Dot Peen marking
- 90° stylus, 50mm long, 4mm diameter, carbide tip
- Supplied with 2 quickly interchangeable facemasks for flat and curved parts
- Top mount handle to ensure marker can be held down firmly while marking


## APPLICATIONS

- Immobile, large/heavy components
- Asset labelling
- Security marking
- Construction applications

Description
Controller is portable, does not require mains power
Drag and drop editor, user admin rights, connectivity; PC required
Marking at 6m or 10m from controller; reduced maximum marking force
Wider / shallower tip angle, IAQG spec, longer
4000 controller with battery power, charger, spare battery and external mains supply



TECHNICAL DATA			<ul><li>Standard</li><li>Optional</li></ul>
Marking area	50mm x 25mm		•
Weight	Head & Cable = 2.3kg; With controller = 7.3kg		•
Nosepiece & stylus	50mm long, 4mm diameter, 90° stylus tip, carbide Various alternatives available		•
Controller	4000 4000 Battery Controller	100V or 240V mains supply 36V, xxAh rechargeable Li-Ion battery	•
Head cable length	3m 6m 10m		• 0 0
Construction	Aluminium internals; tough plastic case		•
Operating temperature	$0^{\circ}$ C - $80^{\circ}$ C ( $32^{\circ}$ F - $176^{\circ}$ F)		•
Supply requirements	240V 50Hz / 100v 60Hz		•
Workpiece hardness	Max. 62 HRC (800HV)		•
Marking type	5 x 7, 7 x 9, Varidot, logo	5 x 7, 7 x 9, Varidot, logos,	
Character sizes	0.15mm – 24.9mm in 0.15	•	



### ACCESSORIES

#### Description

Extended Facemask	Facemask with 2 supports for accessing difficult locations / marking uneven surfaces. Supplied as kit with extended nosepiece and stylus.	
Trolley	For holding and moving controller and marking head	
Base and Column	For fixing P50-25 marker in place for bench-top marking	
Balancer	For suspending	
Spare battery	For optional battery version of 4000 controller	
Barcode Reader	RS232 barcode scanner to select programme or input marking data	
Custom Facemask	Custom-designed facemasks for marking specific components	



Headquarters: 66 Granby St., Bloomfield, CT 06002 
860-286-8728 
Fax: 860-242-3017 Midwest Technical Center: 4861 American Rd., Suite A-B, Rockford, IL 61109

19

ი

25

ശ